








HIJSBAND/RONDSTROP WEBBING SLING/ROUND SLING

WERKLASTEN IN TONNEN WORKING LOAD LIMITS (WLL) IN TONS

NEN 1492-1/2 • TÜV ISO 9001 • TÜV VCA* • EKH • Koninklijke Metaalunie

TYPE BAND		KLEUR COLOUR							
		hoek B angle B	0	0	0°-45°	45°-60°	0°-45°	45°-60°	0
HIJSBAND WEBBING SLING	RONDSTROP ROUND SLING	werklastfactor coefficient	1,0	2,0	1,4	1,0	0,7	0,5	0,8
G-30	R-10	PAARS PURPLE	1,0	2,0	1,4	1,0	0,7	0,5	0,8
G-60	R-20	GROEN GREEN	2,0	4,0	2,8	2,0	1,4	1,0	1,6
G-90	R-30	GEEL YELLOW	3,0	6,0	4,2	3,0	2,1	1,5	2,4
G-120	R-40	GRUIS GREY	4,0	8,0	5,6	4,0	2,8	2,0	3,2
G-150	R-50	ROOD RED	5,0	10,0	7,0	5,0	3,5	2,5	4,0
G-180	R-60	BRUIN BROWN	6,0	12,0	8,4	6,0	4,2	3,0	4,8
G-240	R-80	BLAUW BLUE	8,0	16,0	11,2	8,0	5,6	4,0	6,4
G-300	R-100	ORANJE ORANGE	10,0	20,0	14,0	10,0	7,0	5,0	8,0
240DD6	R-150	ORANJE ORANGE	15,0	30,0	21,0	15,0	10,5	7,5	12,0
300DD6	R-200	ORANJE ORANGE	20,0	40,0	28,0	20,0	14,0	10,0	16,0
300DD8	R-250	ORANJE ORANGE	25,0	50,0	35,0	25,0	17,5	12,5	20,0



VAN GOOL

• hef- en hijstechniek • valbeveiliging • verhuur

T: 0251 291919 • www.vangool.nl